

Day / Night Indoor Speed Dome Camera

MODEL: MP-1101SA / SB



FEATURES :

- !" Sony 216x high speed dome camera (18x optical and 12 x digital zoom)
- !" High speed multi-point detection and auto focusing
- !" RS-485 remote controlling circuit
- !" OSD on screen display menu
- !" Multi-memory, Auto iris function
- !" 128 points pre-cruised function
- !" Advanced spherical privacy zone masking function
- !" IR-Cut switching dual mode day night speed dome camera

SPECIFICATIONS (Note: Design and specifications are subject to change without prior notice.)

Model No.	MP-1101SA / SB
Image Pick-up Device	SONY 1/4" SUPER HAD CCD
Lens	18x Optical Zoom F= 4.1 to 73.8mm (F1.4 to F3.0), Digital 12x
Horizontal Resolution	More than 470 (460) TV lines
Minimum Illumination	0.01 Lux with IR cut on, 1.0 LUX @ F1.4
S/N Ratio	More than 50dB
Electronic Shutter	Auto / Manual : 1/60(1/50) – 10,000sec. 16 steps
Focusing System	Auto (Sensitivity : H,L), one push AF, Manual, Infinity
Pan Rotation Angle	360 degree endless , Manual / program Auto
Pan Rotation Speed	245 degrees / second
Tilt Rotation Angle	5~90 degrees / second , Manual / program Auto
Tilt Rotation Speed	80 degrees / second
Protocol	Pelco P, Pelco D, Lilin, Nicecam at 9600bps
Auto Gain Control	Auto / Manual (-3db to 18db, 3db steps)
Back Light Compensation	ON/OFF switch able
Synchronous System	Internal, Negative sync.
Video Output	1 Vp-p / 75 Ohms.
Power Supply	DC 12V ±10! / 145 MA or AC 90~264 Volts
Operating Temperature	-10 to 50 (14 to 122)